



# TeSys D - auxiliary contact block - 2 NC - screw clamp terminals

LA1DX02

! Discontinued on: Jul 10, 2021

(!) Discontinued

## Main

Range	TeSys
Product Name	TeSys Deca
Product Or Component Type	Auxiliary contact block
Device Short Name	LA1
Range Compatibility	TeSys D CAD TeSys D LC1D TeSys F LC1F TeSys F CR1F TeSys Deca CAD TeSys Deca LC1D
Mounting Location	Front
Pole Contact Composition	2 NC (sealed)
Contacts Operation	Instantaneous
[Ue] Rated Operational Voltage	125 V AC for protected contact 30 V DC for protected contact
[le] Rated Operational Current	0.1 A
[Ui] Rated Insulation Voltage	250 V conforming to IEC 60947-5-1
Standards	EN/IEC 60947-5-1 UL 60947-5-1 CSA C22.2 No 60947-5-1 GB/T 14048.5
Product Certifications	CB UL CSA CCC EAC UKCA

# Complementary

Mechanical Durability	5 Mcycles
Minimum Switching Current	1 mA
Minimum Switching Voltage	5 V
Insulation Resistance	> 10 MOhm
Connections - Terminals	Screw clamp terminals 1 cable(s) 12.5 mm²flexible with cable end Screw clamp terminals 1 cable(s) 12.5 mm²flexible without cable end Screw clamp terminals 2 cable(s) 12.5 mm²flexible with cable end Screw clamp terminals 2 cable(s) 12.5 mm²flexible without cable end Screw clamp terminals 1 cable(s) 12.5 mm²figid Screw clamp terminals 2 cable(s) 12.5 mm²figid

Tightening Torque	1.7 N.m - with screwdriver flat Ø 6 mm 1.7 N.m - with screwdriver Philips No 2	
	1.7 N.m - with screwdriver pozidriv No 2	
Height	48 mm	
Width	44 mm	
Depth	39 mm	
Net Weight	0.04 kg	

# **Environment**

Environmental Characteristic	Harsh environment
Ip Degree Of Protection	IP2X conforming to IEC 60529
Protective Treatment	TH conforming to IEC 60068
Ambient Air Temperature For Storage	-2570 °C
Ambient Air Temperature For Operation	-2570 °C

# **Packing Units**

PCE
1
5.2 cm
4.2 cm
4.8 cm
53.0 g
BB1
10
5.0 cm
8.5 cm
26.0 cm
540.0 g
S02
80
15.0 cm
30.0 cm
40.0 cm
4.613 kg



**Green Premium**<sup>TM</sup> **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

### Well-being performance

<b>Ø</b>	Reach Free Of Svhc	
	Toxic Heavy Metal Free	
<b>Ø</b>	Mercury Free	
<b>②</b>	Rohs Exemption Information	Yes

#### **Certifications & Standards**

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant EU RoHS Declaration
China Rohs Regulation	China RoHS declaration  Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	No need of specific recycling operations