# **Product datasheet**

Specifications





Reversing Contactor, TeSys Deca, 3P(3NO), AC-3/AC-3e, <=440V 80A, 230V AC 50/60Hz coil, screw clamp terminals

LC2D80P7

#### Main

Mann						
Range	TeSys					
Product Name	TeSys Deca					
Product Or Component Type	Reversing contactor					
Device Short Name	LC2D					
Contactor Application	Resistive load Motor control					
Utilisation Category	AC-1 AC-3 AC-3e AC-4					
Device Presentation	Preassembled with reversing power busbar					
Poles Description	3P					
Power Pole Contact Composition	3 NO					
[Ue] Rated Operational Voltage	Power circuit: <= 690 V AC 25400 Hz Power circuit: <= 300 V DC					
[le] Rated Operational Current	125 A (at <60 °C) at <= 440 V AC AC-1 for power circuit 80 A (at <60 °C) at <= 440 V AC AC-3 for power circuit 80 A (at <60 °C) at <= 440 V AC AC-3e for power circuit 55 A (at <60 °C) at <= 400 V AC AC-4 for power circuit					
Motor Power Kw	22 kW at 220230 V AC 50 Hz 37 kW at 380400 V AC 50 Hz 45 kW at 415440 V AC 50 Hz 55 kW at 500 V AC 50 Hz 45 kW at 660690 V AC 50 Hz					
Motor Power Hp (UI / Csa)	20 hp at 200/208 V AC 60 Hz for 3 phases motors 7.5 hp at 115 V AC 60 Hz for 1 phase motors 15 hp at 230/240 V AC 60 Hz for 1 phase motors 25 hp at 230/240 V AC 60 Hz for 3 phases motors 60 hp at 460/480 V AC 60 Hz for 3 phases motors 60 hp at 575/600 V AC 60 Hz for 3 phases motors					
Control Circuit Type	AC at 50/60 Hz					
[Uc] Control Circuit Voltage	230 V AC 50/60 Hz					
Auxiliary Contact Composition	1 NO + 1 NC					
[Uimp] Rated Impulse Withstand Voltage	8 kV conforming to IEC 60947					
Overvoltage Category	III					
[Ith] Conventional Free Air Thermal Current	10 A (at 60 °C) for signalling circuit 125 A (at 60 °C) for power circuit					
Irms Rated Making Capacity	140 A AC for signalling circuit conforming to IEC 60947-5-1 250 A DC for signalling circuit conforming to IEC 60947-5-1 1100 A at 440 V for power circuit conforming to IEC 60947					
Rated Breaking Capacity	1100 A at 440 V for power circuit conforming to IEC 60947					

[Icw] Rated Short-Time Withstand Current	<ul> <li>135 A 40 °C - 10 min for power circuit</li> <li>320 A 40 °C - 1 min for power circuit</li> <li>640 A 40 °C - 10 s for power circuit</li> <li>990 A 40 °C - 1 s for power circuit</li> <li>100 A - 1 s for signalling circuit</li> <li>120 A - 500 ms for signalling circuit</li> <li>140 A - 100 ms for signalling circuit</li> </ul>					
Associated Fuse Rating	10 A gG for signalling circuit conforming to IEC 60947-5-1 200 A gG at <= 690 V coordination type 1 for power circuit 160 A gG at <= 690 V coordination type 2 for power circuit					
Average Impedance	0.8 mOhm - Ith 125 A 50 Hz for power circuit					
[Ui] Rated Insulation Voltage	Power circuit: 600 V CSA certified Power circuit: 600 V UL certified Signalling circuit: 690 V conforming to IEC 60947-1 Signalling circuit: 600 V CSA certified Signalling circuit: 600 V UL certified Power circuit: 1000 V conforming to IEC 60947-4-1					
Electrical Durability	0.8 Mcycles 125 A AC-1 at Ue <= 440 V 1.5 Mcycles 80 A AC-3 at Ue <= 440 V 1.5 Mcycles 80 A AC-3e					
Power Dissipation Per Pole	12.5 W AC-1 5.1 W AC-3 5.1 W AC-3e					
Front Cover	With					
Interlocking Type	Mechanical					
Mounting Support	Plate Rail					
Standards	CSA C22.2 No 14 EN 60947-4-1 EN 60947-5-1 IEC 60947-4-1 IEC 60947-5-1 UL 508					
Product Certifications	UL CSA RINA GOST CCC DNV LROS (Lloyds register of shipping) GL BV UKCA					
Connections - Terminals	Control circuit: screw clamp terminals 1 cable(s) 14 mm²flexible without cable end Control circuit: screw clamp terminals 2 cable(s) 14 mm²flexible without cable end Control circuit: screw clamp terminals 2 cable(s) 12.5 mm²flexible with cable end Control circuit: screw clamp terminals 1 cable(s) 14 mm²solid Control circuit: screw clamp terminals 2 cable(s) 12.5 mm²flexible with cable end Power circuit: connector 1 cable(s) 450 mm²flexible without cable end Power circuit: connector 2 cable(s) 450 mm²flexible without cable end Power circuit: connector 1 cable(s) 450 mm²flexible with cable end Power circuit: connector 1 cable(s) 450 mm²flexible with cable end Power circuit: connector 1 cable(s) 450 mm²flexible with cable end Power circuit: connector 1 cable(s) 450 mm²flexible with cable end Power circuit: connector 1 cable(s) 450 mm²flexible with cable end Power circuit: connector 2 cable(s) 450 mm²flexible with cable end Power circuit: connector 2 cable(s) 450 mm²flexible with cable end Power circuit: connector 2 cable(s) 450 mm²flexible with cable end Power circuit: connector 2 cable(s) 450 mm²flexible with cable end Power circuit: connector 2 cable(s) 450 mm²solid					
Tightening Torque	Control circuit: 1.2 N.m - on screw clamp terminals - with screwdriver flat Ø 6 mm Control circuit: 1.2 N.m - on screw clamp terminals - with screwdriver Philips No 2 Power circuit: 12 N.m - on connector - with screwdriver flat Ø 6 to Ø 8 mm Power circuit: 12 N.m - on connector hexagonal screw head 4 mm Control circuit: 1.2 N.m - on screw clamp terminals - with screwdriver pozidriv No 2					
Operating Time	2035 ms closing 620 ms opening					
Safety Reliability Level	B10d = 1369863 cycles contactor with nominal load conforming to EN/ISO 13849-1 B10d = 20000000 cycles contactor with mechanical load conforming to EN/ISO 13849-1					

Mechanical Durability	4 Mcycles
Maximum Operating Rate	3600 cyc/h 60 °C

## Complementary

Coil Technology	Without built-in suppressor module					
Control Circuit Voltage Limits	0.30.6 Uc (-4070 °C):drop-out AC 50/60 Hz					
	0.81.1 Uc (-4055 °C):operational AC 50 Hz					
	0.851.1 Uc (-4055 °C):operational AC 60 Hz					
	11.1 Uc (5570 °C):operational AC 50/60 Hz					
Inrush Power In Va	245 VA 60 Hz cos phi 0.75 (at 20 °C)					
	245 VA 50 Hz cos phi 0.75 (at 20 °C)					
Hold-In Power Consumption In Va	26 VA 60 Hz cos phi 0.3 (at 20 °C)					
	26 VA 50 Hz cos phi 0.3 (at 20 °C)					
Heat Dissipation	610 W at 50/60 Hz					
Auxiliary Contacts Type	type mechanically linked 1 NO + 1 NC conforming to IEC 60947-5-1					
	type mirror contact 1 NC conforming to IEC 60947-4-1					
Signalling Circuit Frequency	25400 Hz					
Minimum Switching Current	5 mA for signalling circuit					
Minimum Switching Voltage	17 V for signalling circuit					
Non-Overlap Time	1.5 ms on de-energisation between NC and NO contact					
	1.5 ms on energisation between NC and NO contact					
Insulation Resistance	> 10 MOhm for signalling circuit					

### Environment

Ip Degree Of Protection	IP20 front face conforming to IEC 60529					
Climatic Withstand	conforming to IACS E10					
Protective Treatment	TH conforming to IEC 60068-2-30					
Pollution Degree	3					
Ambient Air Temperature For Operation	-4060 °C 6070 °C with derating					
Ambient Air Temperature For Storage	-6080 °C					
Operating Altitude	03000 m					
Fire Resistance	850 °C conforming to IEC 60695-2-1					
Flame Retardance	V1 conforming to UL 94					
Mechanical Robustness	Vibrations contactor open: 2 Gn, 5300 Hz Shocks contactor open: 8 Gn for 11 ms Vibrations contactor closed: 3 Gn, 5300 Hz Shocks contactor closed: 10 Gn for 11 ms					
Height	127 mm					
Width	182 mm					
Depth	158 mm					
Net Weight	3.2 kg					

## **Packing Units**

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	19.0 cm

Package 1 Width	19.0 cm
Package 1 Length	25.5 cm
Package 1 Weight	3.749 kg
Unit Type Of Package 2	\$03
Number Of Units In Package 2	2
Package 2 Height	30 cm
Package 2 Width	30 cm
Package 2 Length	40 cm
Package 2 Weight	7.944 kg

## **Contractual warranty**

Warranty

18 months

## Sustainability Screen Premium

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

## Well-being performance

Reach Free Of Svhc
 Toxic Heavy Metal Free
 Mercury Free
 Rohs Exemption Information Yes
 Pvc Free


#### **Certifications & Standards**

Reach Regulation	REACh Declaration				
Eu Rohs Directive	Compliant EU RoHS Declaration				
China Rohs Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)				
Environmental Disclosure	Product Environmental Profile				
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins				
Circularity Profile	No need of specific recycling operations				

## **Product datasheet**

#### **Dimensions Drawings**

#### Dimensions



LC2 or 2 x LC1	а	b	с	e1	e2	G	G1
D80 and D95 (AC)	182	127	158	13	-	57	96
c, e1 and e2: including cabling.							

## **Product datasheet**

Connections and Schema

#### Wiring

