# **Product datasheet**

Specification





# Reversing contactor, TeSys Deca, 3P(3 NO) - AC-3 - <= 440 V 95 A - 400 V AC coil

LC2D95V7

Discontinued on: Jan 23, 2021

#### (!) Discontinued

#### Main

Mairi						
Range	TeSys					
Product Name	TeSys Deca					
Product Or Component Type	Reversing contactor					
Device Short Name	LC2D					
Contactor Application	Motor control					
	Resistive load					
Utilisation Category	AC-1					
	AC-3					
	AC-3e					
	AC-4					
Device Presentation	Preassembled with reversing power busbar					
Poles Description	3P					
Power Pole Contact Composition	3 NO					
[Ue] Rated Operational Voltage	Power circuit: <= 690 V AC 25400 Hz					
[co]ge	Power circuit: <= 300 V DC					
[le] Rated Operational Current	135 A /at <60 °C\ at <= 600 \/ AC 1 for power sirguit					
[le] Nated Operational Ourrent	125 A (at <60 °C) at <= 690 V AC-1 for power circuit					
	95 A (at <60 °C) at <= 440 V AC-3 for power circuit					
	95 A (at <60 °C) at <= 440 V AC-3e for power circuit 66.7 A (at <60 °C) at <= 400 V AC-4 for power circuit					
Motor Power Kw	25 kW at 220230 V AC 50 Hz (AC-3)					
	45 kW at 380400 V AC 50 Hz (AC-3)					
	45 kW at 415440 V AC 50 Hz (AC-3)					
	55 kW at 500 V AC 50 Hz (AC-3)					
	45 kW at 660690 V AC 50 Hz (AC-3)					
	15 kW at 400 V AC 50 Hz (AC-4)					
	25 kW at 220230 V AC 50 Hz (AC-3e)					
	45 kW at 380400 V AC 50 Hz (AC-3e)					
	45 kW at 415440 V AC 50 Hz (AC-3e)					
	55 kW at 500 V AC 50 Hz (AC-3e)					
	45 kW at 660690 V AC 50 Hz (AC-3e)					
Motor Power Hp (UI / Csa)	20 hp at 200/208 V AC 60 Hz for 3 phases motors					
	7.5 hp at 115 V AC 60 Hz for 1 phase motors					
	15 hp at 230/240 V AC 60 Hz for 1 phase motors					
	25 hp at 230/240 V AC 60 Hz for 3 phases motors					
	60 hp at 460/480 V AC 60 Hz for 3 phases motors					
	60 hp at 575/600 V AC 60 Hz for 3 phases motors					
Control Circuit Type	AC at 50/60 Hz					
[Uc] Control Circuit Voltage	400 V AC 50/60 Hz					
Auxiliary Contact Composition	2 NO + 2 NC					
[Uimp] Rated Impulse Withstand Voltage	8 kV conforming to IEC 60947					
Overvoltage Category	III					

Apr 23, 2024 Life Is On Schneider

[Ith] Conventional Free Air Thermal Current	10 A (at 60 °C) for signalling circuit 125 A (at 60 °C) for power circuit					
Irms Rated Making Capacity	140 A AC for signalling circuit conforming to IEC 60947-5-1 250 A DC for signalling circuit conforming to IEC 60947-5-1 1100 A at 440 V for power circuit conforming to IEC 60947					
Rated Breaking Capacity	1100 A at 440 V for power circuit conforming to IEC 60947					
[lcw] Rated Short-Time Withstand Current	135 A 40 °C - 10 min for power circuit 400 A 40 °C - 1 min for power circuit 800 A 40 °C - 10 s for power circuit 1100 A 40 °C - 1 s for power circuit 100 A - 1 s for signalling circuit 120 A - 500 ms for signalling circuit 140 A - 100 ms for signalling circuit					
Associated Fuse Rating	10 A gG for signalling circuit conforming to IEC 60947-5-1 200 A gG at <= 690 V coordination type 1 for power circuit 160 A gG at <= 690 V coordination type 2 for power circuit					
Average Impedance	0.8 mOhm - Ith 125 A 50 Hz for power circuit					
[Ui] Rated Insulation Voltage	Power circuit: 1000 V conforming to IEC 60947-4-1 Signalling circuit: 690 V conforming to IEC 60947-1 Power circuit: 600 V CSA certified Power circuit: 600 V UL certified Signalling circuit: 600 V CSA certified Signalling circuit: 600 V UL certified					
Electrical Durability	1.2 Mcycles 95 A AC-3 1.3 Mcycles 125 A AC-1					
Power Dissipation Per Pole	12.5 W AC-1 7.2 W AC-3					
Front Cover	With					
Interlocking Type	Mechanical					
Mounting Support	Plate Rail					
Standards	EN/IEC 60947-1 EN/IEC 60947-4-1 EN/IEC 60947-5-1 UL 60947-4-1 UL 60947-5-1 CSA C22.2 No 60947-4-1 CSA C22.2 No 60947-5-1 GB/T 14048.4					
Product Certifications	IECEE CB Scheme UL CSA CCC EAC LROS (Lloyds register of shipping) RINA BV DNV-GL					
Connections - Terminals	Control circuit: screw clamp terminals 1 cable(s) 14 mm²flexible without cable end Control circuit: screw clamp terminals 2 cable(s) 14 mm²flexible without cable end Control circuit: screw clamp terminals 2 cable(s) 12.5 mm²flexible with cable end Control circuit: screw clamp terminals 1 cable(s) 14 mm²solid Control circuit: screw clamp terminals 2 cable(s) 14 mm²solid Control circuit: screw clamp terminals 1 cable(s) 12.5 mm²flexible with cable end Power circuit: connector 1 cable(s) 450 mm²flexible without cable end Power circuit: connector 2 cable(s) 425 mm²flexible with cable end Power circuit: connector 1 cable(s) 450 mm²flexible with cable end Power circuit: connector 2 cable(s) 416 mm²flexible with cable end Power circuit: connector 1 cable(s) 450 mm²solid Power circuit: connector 2 cable(s) 425 mm²solid					
Tightening Torque	Control circuit: 1.2 N.m - on screw clamp terminals - with screwdriver flat Ø 6 mm Control circuit: 1.2 N.m - on screw clamp terminals - with screwdriver Philips No 2 Power circuit: 12 N.m - on connector - with screwdriver flat Ø 6 to �� 8 mm Power circuit: 12 N.m - on connector hexagonal screw head 4 mm					

Operating Time	2035 ms closing 620 ms opening				
Safety Reliability Level	B10d = 1.3 Mcycles contactor with nominal load conforming to EN/ISO 13849-1 B10d = 20 Mcycles contactor with mechanical load conforming to EN/ISO 13849-1				
Mechanical Durability	4 Mcycles				
Maximum Operating Rate	3600 cyc/h 60 °C				

## Complementary

Coil Technology	Without built-in suppressor module					
Control Circuit Voltage Limits	0.30.6 Uc (-4070 °C):drop-out AC 50/60 Hz 0.81.1 Uc (-4055 °C):operational AC 50 Hz 0.851.1 Uc (-4055 °C):operational AC 60 Hz 11.1 Uc (5570 °C):operational AC 50/60 Hz					
Inrush Power In Va	245 VA 60 Hz cos phi 0.75 (at 20 °C) 245 VA 50 Hz cos phi 0.75 (at 20 °C)					
Hold-In Power Consumption In Va	26 VA 60 Hz cos phi 0.3 (at 20 °C) 26 VA 50 Hz cos phi 0.3 (at 20 °C)					
Heat Dissipation	610 W at 50/60 Hz					
Auxiliary Contacts Type	type mechanically linked 1 NO + 1 NC conforming to IEC 60947-5-1 type mirror contact 1 NC conforming to IEC 60947-4-1					
Signalling Circuit Frequency	25400 Hz					
Minimum Switching Current	5 mA for signalling circuit					
Minimum Switching Voltage	17 V for signalling circuit					
Non-Overlap Time  1.5 ms on de-energisation between NC and NO contact 1.5 ms on energisation between NC and NO contact						
Insulation Resistance	> 10 MOhm for signalling circuit					

## **Environment**

Degree Of Protection IP20 front face conforming to IEC 60529				
Climatic Withstand	conforming to IACS E10			
Protective Treatment	TH conforming to IEC 60068-2-30			
Pollution Degree	3			
Ambient Air Temperature For Operation	-4060 °C 6070 °C with derating			
Ambient Air Temperature For Storage	-6080 °C			
Operating Altitude	03000 m			
Fire Resistance	850 °C conforming to IEC 60695-2-1			
Flame Retardance	V1 conforming to UL 94			
Mechanical Robustness	Vibrations contactor open: 2 Gn, 5300 Hz Shocks contactor open: 8 Gn for 11 ms Vibrations contactor closed: 3 Gn, 5300 Hz Shocks contactor closed: 10 Gn for 11 ms			
Height	127 mm			
Width 182 mm				
Depth	158 mm			
Net Weight	3.2 kg			

## **Packing Units**

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	17 cm
Package 1 Width	18 cm
Package 1 Length	24.8 cm
Package 1 Weight	3.735 kg

## **Contractual warranty**

Warranty 18 months



**Green Premium**<sup>TM</sup> **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

## Well-being performance

<b>②</b>	Reach Free Of Svhc	
<b>⊘</b>	Toxic Heavy Metal Free	
<b>⊘</b>	Mercury Free	
<b>⊘</b>	Rohs Exemption Information Yes	
<b>Ø</b>	Pvc Free	

#### **Certifications & Standards**


**Eu Rohs Directive** 

	EU RoHS Declaration
China Rohs Regulation	China RoHS declaration  Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Compliant

## **Dimensions Drawings**

## **Dimensions**



LC2 or 2 x LC1	а	b	С	e1	e2	G	G1
D80 and D95 (AC)	182	127	158	13	_	57	96
c, e1 and e2: including cabling.							

Connections and Schema

Wiring

