Product datasheet

Specification





EasyPact CVS - Vigi CVS100B circuit breaker - 4P/3d - VIJ

LV510541

! Discontinued

Main

Range	EasyPact	
Product Name	EasyPact CVS	
Device Short Name	Vigi CVS100B	
Product Or Component Type	Earth leakage circuit breaker	
Device Application	Distribution	
Poles Description	4P	
Protected Poles Description	3D	
Earth Leakage Protection (Vigi Add On)	With	
[In] Rated Current	25 A at 40 °C	
Network Type	AC	
Utilisation Category	Category AC	
[Icu] Breaking Capacity	40 kA Icu at 220/240 V AC 50/60 Hz conforming to IEC 60947-2	
Trip Unit Name	TM-D	
Trip Unit Technology	Thermal-magnetic	
Trip Unit Rating	25 A at 40 °C	
Protection Type	Short-circuit protection (magnetic) Overload protection (thermal)	

Complementary

[Uimp] Rated Impulse Withstand Voltage	8 kV conforming to EN/IEC 60947-2
Network Frequency	50/60 Hz
Breaking Capacity Code	В
[Ics] Rated Service Breaking Capacity	15 kA at 440 V AC 50/60 Hz conforming to IEC 60947-2 25 kA at 380/415 V AC 50/60 Hz conforming to IEC 60947-2 40 kA at 220/240 V AC 50/60 Hz conforming to IEC 60947-2
Neutral Position	Left
Mechanical Durability	30000 cycles
Electrical Durability	12000 cycles 415 V In conforming to IEC 60947-2
Control Type	Toggle
Neutral Protection Setting	No protection (3D)
Long Time Pick-Up Adjustment Type Ir	Adjustable

Long Time Pick-Up Adjustment Range	0.71 x ln	
Long Time Delay Adjustment Type	Fixed	
[Tr] Long-Time Delay Adjustment Range	200 ms	
Short-Time Delay Adjustment Type	Fixed	
Instantaneous Pick-Up Adjustment Type Ii	Fixed	
Instantaneous Pick-Up Adjustment Range	300 A	
Earth-Leakage Add-On Module Name	ΛΙΊ	
Earth-Leakage Protection Class	Class AC	
Residual Earth-Leakage Sensitity Adjustment Type	Adjustable 3 settings	
[lōn] Residual Earth-Leakage Sensitive Adjustment	0.3 A 0.5 A 0.1 A	
Residual Earth-Leakage Time Delay Adjustment Type	Fixed	
[Δt] Residual Earth-Leakage Time Delay Adjustment	200 ms	
Contact Position Indicator	Yes	
Mounting Mode	Fixed	
Mounting Support	Backplate	
Upside Connection	Front	
Downside Connection	Front	
Connection Pitch	35 mm	
Compatibility Code	CVS100	
Width	140 mm	
Depth	86 mm	
Height	236 mm	

Environment

Standards	IEC 60947-2 EN 60947-2	
Product Certifications	IEC GOST	
Electrical Shock Protection Class	Class II	
Ambient Air Temperature For Operation	-2570 °C	
Ambient Air Temperature For Storage	-5085 °C	

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	13.0 cm
Package 1 Width	14.0 cm
Package 1 Length	23.3 cm
Package 1 Weight	3530.0 g
Unit Type Of Package 2	CAR

Number Of Units In Package 2	4
Package 2 Height	30.0 cm
Package 2 Width	30.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	14.12 kg
Unit Type Of Package 3	PAL
Number Of Units In Package 3	48
Package 3 Height	104.0 cm
Package 3 Width	60.0 cm
Package 3 Length	80.0 cm
Package 3 Weight	176.64 kg

Contractual warranty

Warranty 18 months

Sustainability Screen Premium*

Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance



Mercury Free



Rohs Exemption Information

Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	No need of specific recycling operations Circularity Profile